

DOOR/WINDOW TRANSMITTERS



Actual size



Compact transmitters allow you to use wireless in more applications. They're so small that they almost disappear.

The 5800 Series of door and window transmitters provide the most reliable, convenient and cost effective solutions for security protection. These devices are powerful and versatile enough to help solve even the toughest, most labor intensive installations.

With a demonstrated outdoor range of over a mile, the 5800 Series has the best performance of any transmitters available today. All 5800 Series transmitters send supervisory messages to the control, as well as tamper and low battery notification. The 5800 wireless technology will provide year after year of reliable security.

With Honeywell transmitters, you can put the required sensor in the optimum location cost effectively. The 5800 Series is reasonably priced technology that provides superior security and reduces installation costs. 5800 Series are all with RF frequency 345 MHz & power level about 1 mW.

5814

Ultra-Small Door/Window Transmitter

Although the 5814's compact design slightly decreases its effective range to maintain a long battery life, it is the perfect solution for difficult to reach places and applications where aesthetics and its small size is important (ornate doors/windows, casements, etc.)

- | Extremely compact
- | Features a built-in reed switch and tamper
- | Includes replaceable lithium coin cell battery
- | Dimensions: 1-1/2" H x 1-1/5" W x 3/5" D

5816MN

Door/Window Transmitter

Two zone transmitter with both built-in magnetic reed switches [90° apart] and wired closed circuit contact loop.

- | Features a small design for a hidden professional look
- | Dimensions: 3-1/16" H x 1-9/16" W x 1-5/32" D

DOOR/WINDOW TRANSMITTERS



5816

Door/Window Transmitter

Two zone transmitter with both built-in magnetic reed switches and wired closed circuit contact loop.

| Features a standard white plastic case. Brown cases available in packs of three (5816BR)

| Dimensions: 3-1/16" H x 1-9/16" W x 1-3/16" D



5817

Three Zone Universal Transmitter

Three zone transmitter with three separate contact loops. Primary loop supports normally

open and normally closed applications and fast loop response time. The two auxiliary loops

support conventional normally closed contact applications.

| Features a normal zone response time of 200msec; the fast zone response is 5msec

| Dimensions: 3-1/2" H x 1-9/16" W x 1-3/16" D



5818

Three Zone Universal Transmitter

Contact sensor that provides concealed protection for a door or window.

| Features a tapered cylinder for easy and flush fit

| Includes self-contained transmitter, reed sensor, battery & recessed magnet

| Features a standard white plastic case; brown cases available (5818BR); plastic cover-up plug included

| Use 7/8" drill bit for transmitter

| Use 1/2" drill bit for magnet

Dimensions: Transmitter: 13/16" diameter, 4-7/8" long

Magnet: 1/2" diameter, 1-3/4" long

Ordering Information:

PartNo.	Description
5814	UltraSmallDoor/Window Transmitter
5816MN	Door/WindowTransmitter
5816	Door/WindowTransmitter
5817	ThreeZoneUniversal Transmitter
5818	ThreeZoneUniversal Transmitter